

Steamate* NA0840

condensate corrosion inhibitor

- Reduce condensate corrosion
- Reduce maintenance costs
- Improve boiler system reliability
- Reduce the levels of iron and copper in boiler feedwater

description and use


Steamate NA0840 is a liquid blend of water-soluble neutralising amines designed to meet the specific needs of boiler and condensate systems.

Steamate NA0840 is designed to protect all parts of the condensate system by chemically neutralising any carbonic acid present in the condensate.

problem description

Steam containing carbon dioxide forms a weakly acidic solution “carbonic acid” when condensation occurs. Metal loss due to carbonic acid is one of the major causes of condensate corrosion.

Feedwater alkalinity is the main source of carbon dioxide as bicarbonate and carbonate alkalinity break down at elevated temperatures as follows:



The first decomposition reaction proceeds to 100% completion whereas, the second reaction proceeds to about 80% completion.

At points of condensation, carbon dioxide dissolves in water to form carbonic acid. This depresses the pH of

the condensate and causes etching of the metal. This characteristic acidic corrosion shows up as thinning and grooving of the metal at and below the water level.

If the corrosion is severe, failures could occur in condensate pipe work, vessels and heat exchangers. This would result in costly equipment replacement, maintenance and possible production losses.

Furthermore, iron and copper corrosion products returned to the boiler may cause deposition in areas of high heat flux, resulting in reduced energy efficiency. Iron deposits are very porous and may promote under deposit corrosion, thus reducing boiler reliability.

condensate corrosion protection

Condensate corrosion can be controlled by applying volatile neutralising amines.

Steamate NA0840 contains neutralising amines with distribution characteristics that are designed to provide protection of metal surfaces at points of initial condensation as well as in extended areas of the condensate system.

Neutralising amines perform two functions when applied as condensate corrosion inhibitors. Firstly, they neutralise the acidity imparted to the condensate by carbon dioxide. Secondly, they elevate the pH of the condensate to a range, where iron pick-up is reduced to a minimum.

There are several important properties that govern the effectiveness of a particular neutralising amine.

Find a contact near you by visiting www.suezwatertechnologies.com and clicking on “Contact Us.”

*Trademark of SUEZ; may be registered in one or more countries.

©2017 SUEZ. All rights reserved.

- **Neutralising capacity:** this is simply the quantity of neutralising amine required to neutralise a given quantity of carbon dioxide.
- **Distribution ratio:** this is a measure of the volatility of a neutralising amine under defined conditions.
- **Basicity:** this is a measure of the neutralising amines ability to elevate the pH of the condensate after all the carbon dioxide has been neutralised.

Steamate NA0840 can provide the required volatility, neutralising capacity and basicity for a typical condensate system.

treatment and feeding requirements

feed point – Steamate NA0840 can be fed to the deaerator storage section, feedwater line, steam drum, or steam header.

In some systems, supplemental (“satellite”) feed points may be required to provide optimum system protection. This is especially true in complex multi-pressure steam/condensate systems with flash tanks and high alkalinity boiler feedwater.

feed rate – The required feed rate of Steamate NA0840 depend on many factors particular to a given

installation. The product feed rate is controlled by monitoring condensate pH, iron and copper levels.

dilution - Steamate NA0840 can be fed neat, or diluted to any convenient strength with softened make-up, feedwater or condensate. Neutralising amines can be fed along with most other internal treatment chemicals.

general properties

The physical properties of Steamate NA0840 are shown on the Safety Data Sheet, a copy of which is available on request.

packaging information

Steamate NA0840 is a liquid blend and is available in a wide variety of customised containers and delivery methods. Contact your SUEZ representative for details at www.suezwatertechnologies.com.

safety precautions

A Safety Data Sheet containing detailed information about this product is available on request.